

Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600340

· Trade name: Multifunction spray E-COLL

· Article number: 4317784348973

· UFI: 4JG0-2NAS-Q80S-YRD9

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH **EDE Platz 1** D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

# **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The labelling of an aspiration hazard (Asp.Tox.1 H304) is not required for aerosol dispensers and containers with a sealed spray device (Regulation (EC) 1272/2008, Annex 1,1.3.3). The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 1)

# · Signal word Danger

## · Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

# · Precautionary statements

|      | ······ , ··········   |
|------|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children.  |
| D040 | IZ  |

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dusts or mists.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

#### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:   |  |          |  |  |  |
|---|--|----------|--|--|--|
| CAS: 75-28-5  | isobutane                                      | 50-<100% |  |  |  |
| EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27-xxxx | Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280 |          |  |  |  |

(Contd. on page 3)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

|  |  | ontd. of page 2) |
|--|--|------------------|
| CAS: 64742-48-9<br>EC number: 927-241-2<br>Reg.nr.: 01-2119471843-32-XXXX                          | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics  Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066 | 20-<25%          |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5<br>Reg.nr.: 01-2119486944-21-xxxx  | propane<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280  | 5-<10%           |
| EC number: 918-481-9<br>Index number: 649-327-00-6<br>Reg.nr.: 01-2119457273-39-xxxx               | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics  Asp. Tox. 1, H304 EUH066  | 2.5-10%          |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32-xxxx | butane, pure     Flam. Gas 1A, H220 Press. Gas (Comp.), H280   | 1-<3%            |

 Regulation (EC) No 648/2004 on detergents / Labelling for contents 30 % and more aliphatic hydrocarbons perfumes

· Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 3)

#### **SECTION 5: Firefighting measures**

#### · 5.1 Extinguishing media

#### · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire. Carbon monoxide (CO)

### · 5.3 Advice for firefighters

#### · Protective equipment:

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

#### · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Cool endangered receptacles with water spray.

### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 4)

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:

Filter A/P2

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

(Contd. on page 6)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 5)

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection



· Body protection: Protective work clothing

# **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Colourless
 Solvent-like
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range -42 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 0.6 Vol %
 Upper: 9.4 Vol %
 Flash point: -80 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

• **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density at 20 °C: 0.78 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

 $\cdot \ \, \text{Important information on protection of health} \\$ 

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Change in condition

· Drip point:

· Oxidising properties Not determined.

(Contd. on page 7)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 6)

· Information with regard to physical hazard

classes

· Evaporation rate

Explosives VoidFlammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Not applicable.

· Oxidising gases Void · Gases under pressure Void Void · Flammable liquids · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

#### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Aldehyde

# **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

**CAS: 74-98-6 propane** 

Inhalative LC50/4h >20 mg/m³ (rat)

(Contd. on page 8)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

| (Contd. of page 7) Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics |         |                                |  |  |  |
|--|---------|--------------------------------|--|--|--|
|  |         | >15,000 mg/kg (rat) (OECD 401) |  |  |  |
|  |         | , , , , , ,                    |  |  |  |
|  |         | 3,400 mg/kg (rat) (OECD 402)   |  |  |  |
| Inhalative   | LC50/4h | 13,100 ppm (rat) (OECD 403)    |  |  |  |
| CAS: 106-97-8 butane, pure   |         |                                |  |  |  |
| Inhalative   | LC50/4h | 658 ppm (rat)                  |  |  |  |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

| · Aquatic toxicity:    |   |                                   |  |
|------------------------|---|-----------------------------------|--|
| CAS: 75-28-5 isobutane |   |                                   |  |
|                        | EC50 (48h)  | 69.43 mg/L (daphnia)              |  |
| Hydrocar               | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics |                                   |  |
| Inhalative             | LC50  | >1,000 mg/L (Lepomis macrochirus) |  |
|                        | EC50  | >1,000 mg/l (algae)               |  |
|                        | EL50/48h  | 1,000 mg/l (daphnia)              |  |

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 9)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

| · European waste catalogue |  |  |
|----------------------------|--|--|
| 16 00 00                   | WASTES NOT OTHERWISE SPECIFIED IN THE LIST   |  |
| 16 05 00                   | gases in pressure containers and discarded chemicals   |  |
| 16 05 04*                  | gases in pressure containers (including halons) containing hazardous substances                              |  |
| 15 00 00                   | WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED |  |
| 15 01 00                   | packaging (including separately collected municipal packaging waste)   |  |
| 15 01 04                   | metallic packaging   |  |
| HP3                        | Flammable  |  |
| HP5                        | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity  |  |

## **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

(Contd. on page 10)



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 9)

- · 14.3 Transport hazard class(es)
- · ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2 Gases. · Label 2.1

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Warning: Gases.

· EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) LQ2 · Transport category 2 · Tunnel restriction code D

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 10)

· Signal word Danger

#### · Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dusts or mists.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Chemical safety assessment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

#### · Contact:

Head of Product Safety Department sdb@ede.de

· Date of previous version: 03.06.2024

· Version number of previous version: 306



Printing date 04.06.2024 Version number 307 (replaces version 306) Revision: 04.06.2024

Trade name: Multifunction spray E-COLL

(Contd. of page 11)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· \* Data compared to the previous version altered.

EU ·