

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.06.2024 Version number 308 (replaces version 307) Revision: 10.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600024
- · Trade name: Adhesive spray E-COLL
- · Article number: 4317784409353
- · UFI: XM25-0VV4-380D-AR53

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumersSU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the mixture Adhesives

· 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H22	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	2 H411	Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 1)

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light (Benzene < 0.1%) butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

 \cdot **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Danger van vernpenenner		
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)	25-50%
EINECS: 265-151-9	🚸 Flam. Liq. 2, H225	
Index number: 649-328-00-1	🚯 Asp. Tox. 1, H304	
Reg.nr.: 01-2119475133-43XXXX		
	🔥 Skin Irrit. 2, H315; STOT SE 3, H336	
	EUH066	
	(Conto	d. on page 3)

EU



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	(Cont dimethyl ether Flam. Gas 1A, H220 Press. Gas (Comp.), H280	d. of page 2) 25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	2.5-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Take affected persons out into the fresh air. Do not leave affected persons unattended. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases. Mouth respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Open and handle receptacle with care.

Use only in well ventilated areas.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 4)

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** Store in a cool location. Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed. Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

 Ingredients with limit values that require monitoring at the workplace: 		
CAS: 115-10-6 dimethyl ether		
IOELV Long-term value: 1920 mg/m ³ , 1000 ppm		
CAS: 78-93-3 butanone		
IOELV Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm		

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin.
- Respiratory protection: Not necessary if room is well-ventilated.
 Use suitable respiratory protective device in case of insufficient ventilation.
 Self-contained respiratory protective device.
- · Hand protection



Protective gloves

(Contd. on page 6)



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 5)

• Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm

• Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses

SECTION 9: Physical and chemical properties

Od Information on basis abusised and showing burners

 General Information Colour: Yellow tint Odour: Recognisable Odour threshold: Not determined. Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range -24 °C Flammability Not applicable. Lower and upper explosion limit Lower: 3 Vol % Upper: 18.6 Vol %
• Odour:Recognisable• Odour threshold:Not determined.• Melting point/freezing point:Undetermined.• Boiling point or initial boiling point and boiling range-24 °C• FlammabilityNot applicable.• Lower and upper explosion limit3 Vol %• Lower:3 Vol %• Upper:18.6 Vol %
 Odour threshold: Not determined. Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range -24 °C Flammability Not applicable. Lower and upper explosion limit Lower: 3 Vol % Upper: 18.6 Vol %
 Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Undetermined. 24 °C Not applicable. Vol % Upper: 18.6 Vol %
 Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: 3 Vol %
 Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: 3 Vol %
 Flammability Not applicable. Lower and upper explosion limit Lower: 3 Vol % Upper: 18.6 Vol %
 Flammability Not applicable. Lower and upper explosion limit Lower: 3 Vol % Upper: 18.6 Vol %
 Lower and upper explosion limit Lower: 3 Vol % Upper: 18.6 Vol %
• Upper: 18.6 Vol %
· Flash point: -42 °C
• Auto-ignition temperature: 235 °C
• Decomposition temperature: Not determined.
• pH Not determined.
· Viscosity:
• Kinematic viscosity Not determined.
· Kinematic: 23 °C - 4 mm (ISO 2431)
• Dynamic: Not determined.
· Solubility
• water: Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value) Not determined.
• Vapour pressure: Not determined.
Density and/or relative density
• Density at 20 °C: 0.7 g/cm ³
Relative density Not determined.
• Vapour density Not determined.
9.2 Other information
· Appearance:
· Form: Aerosol
 Important information on protection of health
and environment, and on safety.
Ignition temperature: Product is not selfigniting.
• Explosive properties: Not determined.
· Solvent separation test:
• Organic solvents: 52 %
· VOC (EC) % 705,0 g/l



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

	(Contd. of page 6)
· VOC (EC) g/l	
· VOCV (CH)	100,00 %
· Solids content:	13.0 %
 Change in condition 	
· Drip point:	
 Oxidising properties 	Not determined.
 Evaporation rate 	Not applicable.
Information with record to physical beyond	
 Information with regard to physical hazard classes 	
· Explosives	Void
 Flammable gases 	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
 Oxidising gases 	Void
 Gases under pressure 	Void
 Flammable liquids 	Void
 Flammable solids 	Void
 Self-reactive substances and mixtures 	Void
 Pyrophoric liquids 	Void
 Pyrophoric solids 	Void
 Self-heating substances and mixtures 	Void
· Substances and mixtures, which emit flammab	le
gases in contact with water	Void
 Oxidising liquids 	Void
 Oxidising solids 	Void
· Organic peroxides	Void
Corrosive to metals	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 7)

· LD/LC50 values relevant for classification:			
CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light (Benzene < 0.1%)			
Oral	LD50	>5,840 mg/kg (rat)	
Dermal	LD50	>2,920 mg/kg (rat)	
Inhalative	LC50/4h	>25 ppm (rat)	
CAS: 115-10-6 dimethyl ether			
Inhalative	LC50/4h	308 ppm (rat)	
CAS: 74-9	CAS: 74-98-6 propane		
Inhalative	LC50/4h	>20 mg/m ³ (rat)	
CAS: 78-93-3 butanone			
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	
CAS: 106-97-8 butane, pure			
Inhalative	LC50/4h	658 ppm (rat)	

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- 11.2 Information on other hazards
- Endocrine disrupting properties

CAS: 78-93-3 butanone

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:
- CAS: 78-93-3 butanone
- Inhalative LC50 2,993 mg/L (Lepomis macrochirus)

• 12.2 Persistence and degradability No further relevant information available.

List II



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

(Contd. of page 8)

• **12.3 Bioaccumulative potential** No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Toxic for aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- \cdot ADR, IMDG, IATA

· 14.2 UN proper shipping name

- · ADR
- ·IMDG
- ·IATA

UN1950

UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS AEROSOLS, flammable

(Contd. on page 10)



Printing date 10.06.2024	Version number 308	(replaces version 307)	Revision: 10.06.2024
Trade name: Adhesive spray	E-COLL		
			(Contd. of page 9)
· 14.3 Transport hazard clas	s(es)		
· ADR			
· Class · Label		2 5F Gases. 2.1	
·IMDG			
· Class · Label		2.1 Gases. 2.1	
·IATA			
· Class · Label		2.1 Gases. 2.1	
 · 14.4 Packing group · ADR, IMDG, IATA 		Void	
· 14.5 Environmental hazard	ls:	Product contains environme substances: Naphtha (petro (Benzene < 0.1%)	
· Marine pollutant:		No Symbol (fish and tree)	
· Special marking (ADR):		Symbol (fish and tree)	
 14.6 Special precautions for Hazard identification number 		Warning: Gases. -	
· EMS Number:		F-D,S-U	
 14.7 Maritime transport in instruments 	bulk according to IM(D Not applicable.	
· Transport/Additional inform	mation:		
· ADR · Limited quantities (LQ)		1L	
Transport category Tunnel restriction code		2 D	
			(Contd. on page 11)



Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

Trade name: Adhesive spray E-COLL

· UN "Model Regulation":

(Contd. of page 10) UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light (Benzene < 0.1%) butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Chemical safety assessment
- · Named dangerous substances ANNEX I Methanol
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II
- None of the ingredients is listed.

(Contd. on page 12)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.06.2024

Version number 308 (replaces version 307)

Revision: 10.06.2024

(Contd. of page 11)

Trade name: Adhesive spray E-COLL

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Product safety department
- · Contact: sdb@ede.de
- Date of previous version: 23.05.2021
- Version number of previous version: 307

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.