

Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600014

· Trade name: Cutting oil spray E-COLL

· Article number: 4317784348942

· UFI: 12FN-KMXH-4A0P-6DYC

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Coolant/ Cutting solution
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated heavy paraffinic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8 Reg.nr.: 01-211948627-25-xxxx 01-2119471299-27	Distillates (petroleum), hydrotreated heavy paraffinic ♣ Asp. Tox. 1, H304 Specific concentration limit: Asp. Tox. 1; H304: C ≥ 5 %	50-100%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-10%
	(C)	ontd on page 3)

(Contd. on page 3)



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

	(0	Contd. of page 2)
CAS: 106-97-8	butane, pure	2.5-10%
EINECS: 203-448-7	♠ Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32-xxxx	` ' <i>'</i> '	
CAS: 95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	>0.25-<1%
EINECS: 204-414-9	♦ STOT RE 2, H373	
Reg.nr.: 01-2119777867-13-xxxx	Skin Corr. 1C, H314	
	Aguatic Acute 1, H400; Aguatic Chronic 1, H410	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Acute Tox. 4, H312	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

(Contd. on page 5)



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		(petroleum), hydrotreated heavy paraffinic
Inhalative D	ONEL (worker)	5.6 mg/m³ (professional use)
	ONEL (population)	1.2 mg/m³ (cus)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Hand protection



· Material of gloves

Nitrile rubber, NBR Chloroprene rubber, CR

Penetration time (min.): >480 min.

Recommended thickness of the material: $\geq 0.4 \text{ mm}$

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Colourless

 Characteristic
 Not determined.

 Undetermined.

· Boiling point or initial boiling point and boiling

range -44 °C

Flammability
 Not determined.

The substance is capable of catching fire or being set

on fire.

0.1 hPa

· Lower and upper explosion limit

• **Lower:** 0.9 Vol % • **Upper:** 7.0 Vol %

• **Flash point:** -97 °C (CAS: 74-98-6 propane)

· Auto-ignition temperature: 365 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic**: Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C:

· Density and/or relative density

Density at 20 °C: 0.45 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

Organic solvents: 19,7%
 · VOC (EC) % 30.13 %
 · VOC (EC) g/l 135.9 g/l

Change in condition

Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 7)

(Contd. of page 6)



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

Flammable gases
 Aerosols
 Oxidising gases
 Gases under pressure
 Flammable liquids
 Flammable solids
 Void
 Void
 Void
 Void

Void

· Gases under pressure Flammable liquids · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 647	CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic	
Oral	LD50	>2,000 mg/kg (rat) (OCED 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OCED 402)
	NOEC(14d)	≥1,000 mg/l (Fis)
CAS: 74-9	8-6 propane	
Inhalative	LC50/4h	>20 mg/m³ (rat)
CAS: 106-	-97-8 butane	, pure
Inhalative	LC50/4h	658 ppm (rat)



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

CAS: 95-	38-5 2-(2-he _l	(Contd. of page 7) otadec-8-enyl-2-imidazolin-1-yl)ethanol
Oral	LD50	1,256 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 64742	CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		
LC50 (96h)	>100 mg/L (Pimephales promelas) (OCED 203)		
EC50 (48h)	>10,000 mg/L (Daphnia magna) (OECD 202)		
CAS: 75-28	-5 isobutane		
EC50 (48h)	69.43 mg/L (daphnia)		
CAS: 95-38	-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol		
LC50 (96h)	0.3 mg/L (Brachydanio rerio)		
EC50/72h	0.03 mg/l (Desmodesmus subspicatus)		
EL50/48h	0.136 mg/l (Daphnia galeata)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 8)

- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods:
- · European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



Class
 Label
 2 Gases.
 2.1

· 14.4 Packing group

· **ADR** Void

(Contd. on page 10)



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 9)

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• EMS Number: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling:
 Distillates (petroleum), hydrotreated heavy paraffinic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at:



Printing date 04.06.2024 Version number 311 (replaces version 310) Revision: 04.06.2024

Trade name: Cutting oil spray E-COLL

(Contd. of page 10)

sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact:

Head of Product Safety Department

sdb@ede.de

Date of previous version: 12.11.2020
Version number of previous version: 310

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.