

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· Trade name: Dry lubricant film PTFE E-COLL

· Article number: 4317784636926

· UFI: 6C1R-T4FV-MC00-8DM4

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Lubricant

#### · 1.3 Details of the supplier of the safety data sheet

##### · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
EDE Platz 1  
D-42389 Wuppertal  
Germany

Tel. +49 202 6096-0

e-mail: sdb@ede.de

· Further information obtainable from: Product safety department

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

### SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

##### · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

##### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### · Hazard pictograms



GHS02 GHS07

· Signal word Danger

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 1)

**· Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1A, H220	50-100%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220	10-<25%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

		(Contd. of page 2)
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<25%
EC number: 921-024-6 Reg.nr.: 01-2119486291-36-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225 ☠ Asp. Tox. 1, H304 🐟 Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	2.5-10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:** Personal protection for the First Aider.
- **After inhalation:**  
Supply fresh air.  
Seek medical treatment in case of complaints.
- **After skin contact:**  
Wash with water and acidic soap.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 3)

- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.  
Store in a cool and dry place.

- **Information about storage in one common storage facility:** Store away from oxidising agents.

- **Further information about storage conditions:** Protect from heat and direct sunlight.

- **7.3 Specific end use(s)** No further relevant information available.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021


Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**  
 Protective gloves  

Due to the lack of tests, no recommendation can be made on the glove material for the product / preparation / chemical mixture can be given.
- **Material of gloves**  
Nitrile rubber, NBR  
Recommended thickness of the material:  $\geq 0.4$  mm
- **Penetration time of glove material**  
Value for the permeation: Level 6  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Recommendation: safety glasses with side protection shield

**SECTION 9: Physical and chemical properties**

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Aerosol
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 5)

· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable, as aerosol.
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	0.6 Vol % (CAS: 106-97-8 butane, pure)
· <b>Upper:</b>	10.9 Vol % (CAS: 74-98-6 propane)
· <b>Flash point:</b>	-60 °C
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Kinematic: 23 °C - 4 mm (ISO 2431)</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Fully miscible.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C:</b>	4,000 hPa
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C:</b>	0.57 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	365 °C
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent separation test:</b>	
· <b>Organic solvents:</b>	99.8 %
· <b>VOC (EC) %</b>	99.80 %
· <b>Change in condition</b>	
· <b>Softening point/range</b>	
· <b>Oxidising properties</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 6)

- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**CAS: 106-97-8 butane, pure**

Inhalative LC50/4h 658 ppm (rat)

**CAS: 74-98-6 propane**Inhalative LC50/4h >20 mg/m<sup>3</sup> (rat)**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral LD50 &gt;5,840 mg/kg (rat) (OCED 401)

Dermal LD50 &gt;2,920 mg/kg (rabbit) (OCED 402)

Inhalative LC50/4h 25.2 mg/L (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 7)

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

**· Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:****CAS: 75-28-5 isobutane**

EC50 (48h) 69.43 mg/L (daphnia)

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

EL50 akut (48h) 3 mg/l (Daphnia magna)

LL50/96h 11.4 mg/l (Oncorhynchus mykiss)

EL50/72h 30 mg/l (algae)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**

**· Remark:** Harmful to fish**· Additional ecological information:****· General notes:**

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 8)

**SECTION 13: Disposal considerations****13.1 Waste treatment methods:**

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

**European waste catalogue**

15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging

**Recommended cleansing agents:** Water, if necessary together with cleansing agents.**SECTION 14: Transport information****14.1 UN number or ID number****ADR, IMDG, IATA** UN1950**14.2 UN proper shipping name****ADR** UN1950 AEROSOLS  
**IMDG** AEROSOLS  
**IATA** AEROSOLS, flammable**14.3 Transport hazard class(es)****ADR****Class** 2.5F Gases.**Label** 2.1**IMDG, IATA****Class** 2.1**Label** 2.1**14.4 Packing group****ADR, IMDG, IATA** Void**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**

Warning: Gases.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 9)

- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Methanol
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.07.2021

Version number 301 (replaces version 2)

Revision: 23.07.2021

**Trade name: Dry lubricant film PTFE E-COLL**

(Contd. of page 10)

**· REGULATION (EU) 2019/1148****· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**· Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**· Verordnung (EU) Nr. 528/2012 - Verwendung von Biozidprodukten****· Information about limitation of use:**

Employment restrictions concerning pregnant and lactating women must be observed.

**· Exposure scenario(s)**Exposure scenario(s) of ingredients (if present) are available on request at:  
sdb@ede.de**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.**· Contact:** sdb@ede.de**· Version number of previous version:** 2**· Abbreviations and acronyms:**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3