Revision: 20.02.2024



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 305 (replaces version 304)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600103

· Trade name: Wood Lubricant E-COLL

· Article number: 4317784179621

· UFI: 0QER-UX9Q-3C0D-ET57

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



- · Signal word Danger
- · Hazard statements

H304 May be fatal if swallowed and enters airways.



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101	If medic	cal advid	ce is	needed,	have proc	luct contair	ner or l	abel at h	and.
D 4 0 0					-				

P102 Keep out of reach of children.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
Reg.nr.: 01-2119458869-15-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	50-100%
	Asp. Tox. 1, H304 Aquatic Chronic 3, H412	
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2 Reg.nr.: 01-2119480375-34-xxxx	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	25-50%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation: Supply fresh air.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 2)

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Not required.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.

(Contd. on page 4)



Printing date 20.02.2024

Version number 305 (replaces version 304)

Trade name: Wood Lubricant E-COLL

(Contd. of page 3)

Revision: 20.02.2024

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Well cosed, protected from light.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale dust / smoke / mist.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Recommendation: safety glasses with side protection shield



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Yellow
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined. • Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: 66 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

• Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Solution

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

• Organic solvents: 0.0 %

· VOC (EC) g/l

· VOCV (CH) 0,00 %

Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard

classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

(Contd. on page 6)



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

		(Contd. of page 5)
· Flammable liquids	Void	, , , ,
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	
•		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
Oral	LD50	>5,060 mg/kg (rat)			
Dermal	LD50	3,400 mg/kg (rabbit)			
Inhalative	LC50/4h	13,100 mg/m³ (rat)			
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic					
Oral	LD50	5,000 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rat)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 6)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity: Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
EC50	10-22 mg/l (daphnia) (OECD 202)			
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic				
EC50 (21d)	>10 mg/L (Daphnia galeata)			
EC50 (48h)	>10,000 mg/L (Daphnia galeata)			
NOEC (21d)	10 mg/l (Daphnia galeata)			

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR

· Class - (-)
· Label -

· ADN/R Class: Void

· IMDG, IATA

· Class Void

· Label

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· EMS Number:

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 9)



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 8)

· Hazard pictograms



· Signal word Danger

· Hazard statements

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I Methanol

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Verordnung (EU) Nr. 528/2012 Verwendung von Biozidprodukten applicable
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

Date of previous version: 15.02.2023
Version number of previous version: 304

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic



Printing date 20.02.2024 Version number 305 (replaces version 304) Revision: 20.02.2024

Trade name: Wood Lubricant E-COLL

(Contd. of page 9)

vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

- EU ---